

H&DMARK

Fisa tehnica: Laser rotativ ECO 600HV



Telemetre laser

Detectoare

Laseri multipunct

Laseri liniari

Laseri multilinie

Laseri cruce

Laseri multicruce

Laseri rotativi

Laseri combinati

Nivele laser

Nivele optice

Teodoliti

Trepiede

Mire

Jaloane

Goniometre

Umidometre

Decibelmetre

Accesorii

Date tehnice:		Se livreaza cu:
Autoorizantalizare	$\pm 5^{\circ}$, motorizata	Laserul rotativ ECO 600HV
Timp de autoorizantalizare	< 30 sec.	Receptor laser Acceptor
Precizie (orizontala)	± 1 mm/ 10m	Support fixare receptor
Precizie (verticala)	± 1 mm/ 10m	Telecomanda IR
Diam. de lucru (cu receptor)	300 m	Incarcator 220V
Reglarea inclinarii (axa X)	Da, manuala,	Baterie
Reglarea inclinarii (axa Y)	Da, manuala,	Manual de utilizare
Reglarea inclinarii (axa X si Y)	---	Cutie de transport
Viteza de rotatie [rpm]	0, 60, 120, 300, 600 rot/min.	
Alimentare	Acumulatori NiMH, 4,8V,3800 mAh	
Timp de operare [h]	~ 30 h	
Posibilitate control la dist.	Da, telecomanda, ~25m	
Temperatura de lucru	-20 ÷ + 50 °C	
Clasa laserului	3R	
Puterea laserului	< 5 mW	
Lungimea de unda	635 nm	
Clasa de protectie	IP 54	
Fizare pe trepid	Filet 5/8"	
Dimensiuni [mm]	150 x 200 x 190 mm	
Greutate [kg]	2,1 kg	